

GLAZE COAT GLOSS

CODE:

ACG

DESCRIPTION:

Glazecoat Gloss is a water based pure acrylic blend with excellent clarity and hardness. Recommended for interior/exterior surfaces where a sheen and durable finish is required. Imparts a durable dirt resistant coating.

PRODUCT BENEFITS:

Provides a non-yellowing film with long term wear resistance. Imparts aesthetic appeal over other finishes. Easy to apply by brush or roller. Resists dirt collection and makes cleaning easier.

SURFACE PREPARATION:

Surfaces must be clean and dry. Apply 1 - 2 coats. 1 coat is sufficient for general maintenance.

PRECAUTIONS:

Do not apply during cold, wet conditions.
Do not apply directly to unprimed metal surfaces.
Not suitable for floors.

APPLICATION:

Stir thoroughly with flat paddle before use. Ready for use by brush or roller. Thin with clean water for spraying. Clean up with water.

TECHNICAL DATA:

| | |
|---------------------------------|---|
| Type: | Pure acrylic polymer. |
| SG: | 1.01 - 1.05 |
| Drying Time: (T) @ 25°C (H): | 1/2 - 1 hour 4 hours |
| Recoat: | 4 hours |
| Finish: | Gloss |
| Viscosity: | 50 - 60 seconds Ford Cup 4 |
| Solids Volume: | 18 - 22% |
| Solids Mass: | 31 - 33% |
| Spread Rate: | Approx. 10m ² /Lt depending on surface profile and porosity. |
| Flashpoint: | Non-flammable |
| Colour Range: | Clear |
| Pack Size: | 1L & 5L |

Health and Safety:

Refer to Material Safety Data Sheet