

GLOSS VARNISH

CODE:**TGV****DESCRIPTION:**

Trade Gloss Varnish is used for the decoration and protection of interior and most exterior wooden surfaces where a durable rich gloss finish is preferred. Used extensively on wooden window frames, doors, weatherboards etc.

PRODUCT BENEFITS:

Provides exterior timber with excellent durability. The deep rich gloss with its unique transparent pigments, repels the sun's harsh ultra violet rays to retard degradation and prevent premature embrittlement of the coating. Has been formulated to stain and protect exterior wooden surfaces.

SURFACE PREPARATION:

NEW: Surface must be clean, dry and well sanded. Thin first coat up to 20% with Mineral Turps in order to aid penetration. Thin second coat 10%. Third and fourth coats to be applied undiluted. Sand lightly between coats.
PREVIOUSLY VARNISHED: Surfaces in sound condition should be well sanded. For maximum protection apply 3 coats with 24 hours drying time between coats. Surfaces in poor condition must be stripped back to bare wood then proceed as for new timber.

PRECAUTIONS:

Do not apply to wet/damp timber. Important to treat the end grain of all exposed exterior timber to prevent the ingress of moisture. Not recommended for floors.

APPLICATION:

Stir thoroughly with flat paddle before use. Ready for use by brush. For conventional spray thin up to 20% with Mineral Turps. Will require several coats to give the required build and gloss. Thin and clean up with Mineral Turps.

TECHNICAL DATA:

Type:	Long Oil Alkyd
SG:	0.88 - 0.92
Drying Time: (T) @ 25°C (H):	4 Hours 24 Hours
Recoat:	24 Hours
Viscosity:	60 - 80 seconds Ford Cup 4 @ 25°C
Spread Rate:	Approx. 12m ² /L depending on surface porosity.
Flashpoint:	35°C
Solids Volume:	33 - 36%
Solids Mass:	41 - 45%
Finish:	High gloss
Colour Range:	Clear, Dark Oak, Light Oak, Teak & Mahogany
Pack Size:	500ml, 1L & 5L

Health and Safety:

Refer to Material Safety Data Sheet