



TRADE RANGE

TECHNICAL
DATA SHEET

NAC™
NATAL
ASSOCIATED
CHEMICALS

LOW SHEEN

CODE:

TPA

DESCRIPTION:

Low Sheen is a quality fully washable interior/exterior pure acrylic wall coating that dries to a low sheen finish. Suitable for direct application to new and previously painted plaster, fibre cement and composition boards. Can be used with confidence in homes, hotels, flats and other areas that require a fully washable, durable, stain resistant, low sheen paint.

PRODUCT BENEFITS:

Easily applied by brush, roller or airless spray. Quick drying. Low odour. Non-yellowing. Easy clean up with water.

SURFACE PREPARATION:

Surface to be painted must be thoroughly clean, dry and free from all foreign contaminants. Loose, flaking paint and efflorescence must be completely removed from previously painted surfaces. All bare exposed metal areas must be spot primed with the appropriate primer and undercoat. Gloss and oil paint surfaces to be thoroughly sanded and wiped down with damp cloth. Chalky surfaces must be thoroughly sanded before applying 1 coat Plaster Primer diluted 10% with Mineral Turpentine. Kitchen walls without exception to be washed down with sugar soap.

GENERAL:

Do not apply in cold and wet weather conditions.
Do not apply to unprimed metal surfaces.

APPLICATION:

Stir thoroughly with flat paddle before use. Ready for use by brush, roller or airless spray. Thinning not normally necessary. Clean up with water.

TECHNICAL DATA:

Type:	Pure Acrylic.
SG:	+/- 1.30
Drying Time: (T) @ 25°C (H):	1 hour 4 hours
Recoat:	4 hours
Finish:	Low Sheen
Viscosity:	100 - 110 KU
Solids Volume:	+/- 31%
Solids Mass:	+/- 47%
Spread Rate:	Approx. 10m ² /Lt depending on surface profile and porosity.
Flashpoint:	Non-flammable
Colour Range:	White and tint bases
Pack Size:	5L & 20L

Health and Safety:

Refer to Material Safety Data Sheet

Note: Certain transparent colours may require a minimum of 3 coats to achieve total obliteration.