



TRADE RANGE

TECHNICAL
DATA SHEET

NACTM
NATAL
ASSOCIATED
CHEMICALS

PREMIUM MATT

CODE:

TPM

Description:

A high quality matt washable finish for interior and exterior use.

Product Benefits:

Provides high opacity.
Provides excellent exterior durability.

SURFACE PREPARATION:

New Work:

1. Concrete and plaster surfaces must be primed with Masonry Primer.
2. Wooden surfaces must be primed with Wood Primer.
3. Metal surfaces must be primed with RP4, excluding smooth surfaces e.g. New Mild Steel, Galvanising or Aluminium which must be coated with Vinyl Wash Primer/ Acid Etch Primer.

Previously Painted Surfaces:

1. Surfaces must be in sound condition.
2. Loose and flaking paint must be removed.
3. Old enamel or oil paints must be sanded and suitably primed.
4. Chalky surfaces must be well brushed and sealed with Masonry Primer.

General:

1. All substrates should be clean, dry, sound and free of grease and oils before painting.
2. Hairline cracks, imperfections should be filled with a suitable Masonry Crack Filler, and primed with Masonry Primer, before application of the paint system.
3. Consult our sales staff for application onto any other substrate.

APPLICATION:

Ready to use with brush, roller or airless spray application. Apply 2 coats.
Clean with water.

TECHNICAL DATA:

SG: +/- 1.47 +/- 0.05
Viscosity: 92 - 98 KU
Drying Time: (T) 2 hours
@ 25°C (H): 4 hours
Overcoating: 4 hours
Solid Mass: +/- 55%
Finish: Matt. Bases very low sheen.
Spread rate: Approx. 8m²/Lt depending on surface porosity
Colour Range: White & bases
Scrubs: > 10 000